

# STP-2

Item ref: 128.513UK

## Stereo Phono Preamplifier

User Manual



Caution: Please read this manual carefully before operating  
Damage caused by misuse is not covered by the warranty

### Introduction

Thank you for choosing the STP-2 stereo phono preamplifier as part of your audio system. This unit has been designed to allow vinyl turntables to be connected to line level or auxiliary inputs, whilst delivering the best sound quality possible.

### Setup and Connection



- Ensure turntable is fitted with a magnetic cartridge
- Connect phono outputs from the turntable to the inputs (1) of the STP-2 via good quality RCA leads
- Connect the outputs (4) from the STP-2 to the line or auxiliary inputs of the mixer or amplifier
- Connect the supplied 9V power adaptor to the DC jack (3) and move the slide switch (2) to "ON"
- The STP-2 will now boost the turntable output from phono to line level
- The front of the STP-2 can pivot open to reveal the battery compartment allowing a PP3 battery to be used if preferred

### Specifications

Power supply	9V DC, 100mA (or optional PP3 battery)
Equalization	RIAA correction
Frequency response	30Hz - 20kHz
Gain	34dB
Input impedance	50k ohms
Output impedance	50k ohms
Dimensions	30 x 70 x 90mm
Weight	250g



**Disposal:** The "Crossed Wheelie Bin" symbol on the product means that the product is classed as Electrical or Electronic equipment and should not be disposed with other household or commercial waste at the end of its useful life. The goods must be disposed of according to your local council guidelines.

#### Errors and omissions excepted.

Copyright© 2021 AVSL Group Ltd, Unit 2 Bridgewater Park,  
Taylor Road, Trafford Park, Manchester. M41 7JQ.

AVSL (Europe) Ltd, Unit 3D North Point House,  
North Point Bus. Park, New Mallow Road, Cork, Ireland.